# ISOFLEX® TEL 3000 ALTEMP Sliding grease



#### **Description:**

ISOFLEX TEL 3000 ALTEMP is a light-coloured, dynamically light lubricating grease for friction points in the textile and precision engineering industry. It consists of ester oil, mineral oil, lithium soap and ALTEMP, a special solid lubricant combination.

### Application:

Owing to ist good low-temperature properties, ISOFLEX TEL 3000 ALTEMP is suitable for plain and rolling bearings, including those used in automotive engineering. It has also proven effective as a low-friction grease for zig-zag winding guides used in the textile industry.

#### **Application notes:**

The lubricant is applied to the clean friction point by brush, spatula, or similar devices. Owing to the different compositions of elastomers and plastic materials, compatibility tests are indispensable before series application.

#### Minimum shelf life:

The minimum shelf life is approx. 24 months if the product is stored in the original closed container in a dry place.

#### Pack sizes:

1 kg can 25 kg bucket

#### **ISOFLEX TEL 3000 ALTEMP**

- Low-friction grease with emergency operating properties
- Efficient lubricating film
- Good corrosion protection
- Long maintenance intervals
- Clean lubrication

#### Product data:

Colour	light beige
Texture	homogeneous, short-fibred
Service temperature range*, °C, approx.	– 45 to 60
Drop point, DIN ISO 2176, °C, approx.	140
Density, at 20 °C, g/cm <sup>3</sup> , approx.	0.84
Worked penetration, DIN ISO 2137, (ASTM D 217); 0.1 mm	280 to 310
Copper corrosion, DIN 51 811, 24 h / 60 °C, corrosion rating	1 – 60
Base oil viscosity, DIN 51 562/1, at 40 °C, mm²/s, approx. at 100 °C, mm²/s, approx.	19.0 4.5
Apparent dynamic viscosity, Klüber viscosity grade***	L

<sup>\*</sup> Service temperatures are guide values which depend on the lubricant's composition, the intended use and the application method. Lubricants change their consistency, apparent dynamic viscosity or viscosity depending on the mechanodynamical loads, time, pressure and temperature. These changes in product characteristics may affect the function of a

<sup>\*</sup> Klüber viscosity grades: EL = extra light lubricating grease; L = light lubricating grease; M = medium lubricating grease; S = heavy lubricating grease; ES = extra heavy lubricating grease

## ISOFLEX® TEL 3000 ALTEMP

## Safety Data Sheet

1.1 Product name: ISOFLEX TEL 3000 ALTEMP

005 060 Code-No.:

08.03.2000

1.2 Klüber Lubrication München KG

Geisenhausenerstraße 7 D-81379 München

Emergency telephone no.: ++49 - 89 7876 - 0

Tel. ++49 - 89 78 76 - 0 telephone exchange Fax: ++49 - 89 78 76 - 333

#### Composition / information on ingredients

Chemical characterization (preparation): Mineral oil, ester oil, lithium soap, inorganic solid lubricants

#### Hazards identification

No particular hazards known

#### First aid measures

After inhalation: Not applicable

After contact with skin: Wash off with soap and plenty of water

After contact with eyes: Rinse with plenty of water

After ingestion: Do not induce vomiting. Obtain medical attention

Advice to doctor: Treat symptomatically

#### Fire-fighting measures

Suitable extinguishing media: Water spray, foam, dry powder, carbon dioxide  $(\mathsf{CO}_2)$ 

Unsuitable extinguishing media: High volume water jet

Special Hazards: In case of fire the following can be released: Carbon monoxide, hydrocarbons

Special protective equipment for firefighters: Standard procedure for chemical fires

Additional information: Water mist may be used to cool closed containers. In the event of fire and/or explosion do not breathe fumes

#### Accidental release measures

Personal precautions: Not required

Environmental precautions: Do not flush into surface water or sanitary

Methods for cleaning up / taking up: Use mechanical handling equipment. Dispose of absorbed material in accordance with the regulations Additional information: None

#### Handling and storage

Advice on safe handling: No special handling advice required Advice on protection against fire and explosion: No special precautions required

Requirements on storage rooms and vessels: No special storage conditions required

Incompatible materials: Incompatible with oxidizing agents. Do not store together with food

Further information on storage conditions: Store at room temperature in the original container

#### Exposure controls / personal protection

Additional advice on system design: Not applicable Ingredients and specific control parameters: None

Respiratory protection: No special protective equipment required

Hand protection: No special protective equipment required

Eye protection: No special protective equipment required

Body protection: No special protective equipment required

Other protection measures: No special protective equipment required

General protection and hygiene measures: Avoid prolonged and/or repeated contact with skin. Remove soiled or soaked clothing immediately. Clean skin thoroughly after work; apply skin cream

without notice. Freudenberg Klüber Lubrication München KG, a member of the Freudenberg group

#### Physical and chemical properties

Form paste Colour beige Odour characteristic

Drop point ~ 140 °C, DIN ISO 2176 > 200 °C (base oil) Flash point Flammability not applicable not applicable Ignition temperature not applicable Autoflammability Lower explosion limit not applicable Upper explosion limit not applicable Vapour pressure-first not applicable

approx. 0.84 g/cm<sup>3</sup>, 20 °C Density Water solubility insoluble

pH value not applicable Kinematic viscosity not applicable

Further information none

#### 10. Stability and reactivity

Conditions to avoid: None

Materials to avoid: Strong oxidizing agents

Hazardous decomposition products: None under normal use

Additional information: None

#### 11. Toxicological information

The toxicological data has been taken from products of similar composition

Acute toxicity: LD<sub>50</sub>/oral/rat = > 2 g/kg (literature data)

Chronic toxicity: None

Human experience: Prolonged skin contact may cause skin irritation

and/or dermatitis

#### 12. Ecological information

Information on elimination (persistence and degradability): Product is insoluble in water. May be separated out mechanically in purification

Behaviour in environmental compartments: Ecological injuries are not known or expected under normal use

Ecotoxic effects: Aquatic toxicity is unlikely due to low solubility Additional information: Should not be released into the environment

#### 13. Advice on Disposal

Disposal: Can be incinerated when in compliance with local, state and federal regulations

Dispose of contaminated packaging and recommended cleaning: Offer rinsed packaging material to local recycling facilities

#### 14. Transport information

GGVS / GGVE: not applicable ADN / ADNR: not applicable IMDG-Code: not applicable ICAO / IATA-DGR: not applicable

Further information: Not classified as dangerous in the meaning of

transport regulations

#### 15. Regulatory information

Labelling according to EU-guidelines: The product does not require a hazard warning label in accordance with EC-directives/German regulations on dangerous substances

National regulations

Issue-department of Safety Data Sheet: Chemical Documentation, Tel.: ++49 - 89 7876 - 564

The data in this product information is based on our general experience and knowledge at the time of printing and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary tests with the selected product. We recommend contacting our Technical Consulting Staff to discuss your specific application. If required and possible we will be pleased to provide a sample for testing. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this product information at any time